



Total Quality. Assured.

**TEST REPORT**



中国认可  
国际互认  
检测  
TESTING  
CNAS L0220

Number: GZHT91050971

Date: Jul 12, 2021

Applicant: JUHUA SHOES CO.,LTD.  
XIBIAN INDUSTRIAL DISTRICT,  
CHENDAI TOWN,JINJIANG CITY,  
FUJIAN,CHINA  
Attn: LILY

**Sample Description:**

Three (3) pairs of submitted samples said to be Men's Cemented lace up low cut safety shoes in Black.

Standard : ASTM F2413-18  
Size : US 9  
Buyer's Name : --  
Ref. No : 200134/200134W  
Brand : --  
Manufacturer : --  
Colour : --  
Vendor : --  
Supplier : --  
P.O. No. : --  
Ref. : --  
Country Of Origin : --  
Goods Exported To : U.S.A.  
Date Received/Date Test Started: Jul. 05, 2021  
Date Final Information Confirmed: --

Test Result Please Refer To Attached Page(S).

Should you have any query on this report, you may contact at [gzfootwear@intertek.com](mailto:gzfootwear@intertek.com)

Authorized By:  
For Intertek Testing Services Shenzhen Ltd.  
Guangzhou Branch

Guiliang Dong  
Senior Lab Manager



Page 1 Of 3

/ nicoleho

**Intertek Testing Services Shenzhen Ltd. Guangzhou Branch**  
深圳天祥质量技术服务有限公司广州分公司  
Room 02, 1-8/F. & Room 01, E101/E201/E301/E401/E501/E601/E701/E801,  
No.7-2, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, Guangdong, China  
广州经济技术开发区科学城彩频路7号之二第1-8层02房、01房101、  
E201、E301、E401、E501、E601、E701、E801  
Tel: +86 208213 9001 Fax: +86 20 82089909 Postcode: 510663



Total Quality. Assured.

## TEST REPORT

Tests Conducted (As Requested By The Applicant)



中国认可  
国际互认  
检测  
TESTING  
CNAS L0220

Number: GZHT91050971

- 1 Protective Toe Impact Resistance (I) (ASTM F2412-18a, 5, Impact Force: 101.7 J (75 lbf), Testing Performed At 22°C And 50% RH)

		<u>ASTM F2413-18 Requirement</u>	<u>Pass / Fail</u>
	Interior Height Clearance		
Left:	13.8 mm	≥ 12.7 mm	Pass
Right:	13.5 mm	≥ 12.7 mm	Pass
Left/Right:	-	≥ 12.7 mm	-

- 2 Protective Toe Compression Resistance (C) (ASTM F2412-18a, 6, Compression Force: 11 121 N (2 500 lbf), Testing Performed At 22°C And 50% RH)

		<u>ASTM F2413-18 Requirement</u>	<u>Pass/Fail</u>
	Interior Height Clearance		
Left:	24.1 mm	≥ 12.7 mm	Pass
Right:	23.2 mm	≥ 12.7 mm	Pass
Left/Right:	-	≥ 12.7 mm	-

/ nicoleho

Page 2 Of 3



End Of Report

*This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. No copy of the test report(except for full text copy) shall be made without the written approval by Intertek.*